



VIEWRAIL

FLIGHT Cantilever

Minimalism to the Max



Specifications

Support

Wall-mounted brackets

Interior - Mild Steel
Exterior - Stainless Steel
Field Adjustable for level and plumb

Configurations

Flexible for nearly any configuration

Tread Types

Wire brushed
Thick (4 1/4" - 5 1/4")
Width (36" - 66")
Interior - Wood
Exterior - Porcelain

Tread Spacing



Open-riser design

Conditions



Residential or commercial
Interior or Exterior
Wood framed
Steel Framed
CMU

Upgrades

LED treads
LED handrail
Grip strips







Wall Specifications




Wall Bracket

Wall Brackets are installed on every side of each “bunch” of LVLs. These support the wall plates that are installed in the next step.


DOCUMENT UNCONTROLLED IF REMOVED, DOWNLOADED, OR EXPORTED FROM AUTODESK VAULT




 Sheet 1 of 1	Part Name: Part Description:	Tolerance: .X" +/- .03" .XX" +/- .015" .XXX" +/- .005" X/X" +/- 1/16" X° +/- 0.5° Or as Specified
	Material:	

Wall Plates


Wall plates are the main backbone for the cantilever system. They are installed by drilling through the wall brackets and through bolting the two pieces together through the slots. Lag screws are then run through the slots as well into the stacked LVLs. The brackets are aligned with the tabs at the top and bottom. Note: the 3/4" plywood is cut out around these plates.




Bottom



Middle




Top




Landing

Wall Plates Installed


DOCUMENT UNCONTROLLED IF REMOVED, DOWNLOADED, OR EXPORTED FROM AUTODESK VAULT




	Part Name: Cantilever Wall	Tolerance: .X" +/- .03" .XX" +/- .015" .XXX" +/- .005" X/X" +/- 1/16" X° +/- 0.5° Or as Specified
	Part Description: Plate	
Sheet 1 of 1	Material:	

Cradle & Platform Arm


The cradle & platform bracket fully support each tread and glass panel and tie into the wall plates with bolts and partite epoxy. Once they are installed then the system is ready for the wood treads.




Cradle




Platform Arm



Cradle & Platform Arm Assembly



Tread Details





Viewrail's Cantilever treads are designed to wrap around the steel arms of the cantilever brackets. They come in two part L pieces that are joined together onsite with wood glue around the bracket. The end caps are attached after the glass is put up and can be siliconed on to prevent them from coming off.




Glass Hardware

The glass on cantilever is attached secured with a bolt that threads into the platform bracket. The hardware assembly contains a plastic stud that the glass sits on, an inner and outer black PETG plastic that isolates the glass from any metal, a metal outer clamp plate, and two pins that sandwich the assembly together and hold on the outer tread cap.



Example: Engineering Approval Documents (9-13)

We meticulously incorporate all specifications into our engineering documents, tailoring each project to your unique requirements. From individual stringers and treads to glass panels, every element is meticulously designed to seamlessly integrate into your environment. These documents serve as your blueprint, allowing you to verify every measurement and finish, ensuring that your project arrives and fits precisely as envisioned within your custom space.



ORDER NUMBER:
 JOB TYPE: Residential (Interior)
 TREAD MATERIAL: WHITE OAK
 TREAD FINISH: NATURAL 5 SHEEN, NO WIREBRUSH
 LED: NO
 GLASS CAP RAIL: 6008 WHITE OAK, NATURAL 5 SHEEN
 CUSTOMER SUPPLIED NOSING: YES
 STAIR INFILL: MONOLITHIC GLASS 1/2"
 TOTAL RUN: 177.125 in
 TOP NOSING DEPTH: 1.5 in
 TREAD NOSING: 1.5 in
 NUMBER OF TREADS: 16
 TREAD SIZE: 48 in X 12.4375 in X 4.25 in
 TREAD RISE: 6.985 in
 TREAD RUN: 10.9375 in
 BOTTOM FINISHED FLOOR THICKNESS: 0.375 in
 TOP FINISHED FLOOR THICKNESS: 0.375 in
 FINISH FLOOR TO FINISH FLOOR: 118.75 in
 SUBFLOOR TO SUBFLOOR: 118.75 in

FINAL DESIGN



STRINGER STYLE:
Cantilever



DRAWN BY: DLE	DATE: 2/2/2024	SIZE: A	SCALE: 0.02 : 1	ORDER NUMBER:	REV: 1
-------------------------	--------------------------	-------------------	---------------------------	---------------	------------------

SHEET NAME: Cover Page

JOB TYPE: Residential (Interior)

TOTAL RUN: 177.125 in

TOP NOSING DEPTH: 1.5 in

TREAD NOSING: 1.5 in

NUMBER OF TREADS: 16



TREAD SIZE: 48 in X 12.4375 in X 4.25 in

TREAD RISE: 6.985 in

TREAD RUN: 10.9375 in

BOTTOM FINISHED FLOOR THICKNESS: 0.375 in

B TOP FINISHED FLOOR THICKNESS: 0.375 in



STRINGER STYLE:
Cantilever



DRAWN BY:

<AUTHOR>

DATE:

2/2/2024

SIZE:

A

SCALE:

0.02 : 1

ORDER NUMBER:

REV:

1

SHEET NAME: CUSTOMER ELEVATION-Cantilever 01

2

1

1/2 Drywall
 3/4 Plywood
 7 1/4 LVL

Angle Bracket

1/2 GLASS

16.00 16.00

Custom LVL Wall:



STRINGER STYLE:
 Cantilever



DRAWN BY:

DATE:

SIZE:

SCALE:

ORDER NUMBER:

REV:

<AUTHOR>

2/2/2024

A

0.02 : 1

1

SHEET NAME:

BLOCKING WALL DETAILS-Cantilever 01

2

1

2


1

B

B

A

A



STRINGER STYLE:
Cantilever



DRAWN BY:

DATE:

2/2/2024

SIZE:

A

SCALE:

0.02 : 1

ORDER NUMBER:

REV:

1

SHEET NAME:

GLASS LAYOUT SIDE-Cantilever 01

2


1

2

1

B

B





Qty: 1 19 ft

A

A

Caprail Layout Map:

Map displays the location of a piece of caprail designated by the ship length of the caprail.

	STRINGER STYLE: Railing				
DRAWN BY: <DLE>	DATE: 2/2/2024	SIZE: A	SCALE: 0.03 : 1	ORDER NUMBER:	REV: 1
SHEET NAME: Caprail Layout					

2

1